## White 9500T Silent Diesel Generator Electric Start Silent Generator

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time: 15-20 work

China

- Payment Terms:
- GET ISO CE Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



## **Product Specification**

| <ul> <li>Rated Frequency:</li> </ul>                  | 50hz 60hz  |
|---|--|
| <ul> <li>Rated Output(kw):</li> </ul>                 | 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3              |
| <ul> <li>Max Output (kw):</li> </ul>                  | 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7              |
| <ul> <li>Rated Voltage (V):</li> </ul>                | 220V Or As Request                                       |
| • Rated Currency (A):                                 | 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/<br>27.2 28.6 |
| <ul> <li>Rated Rotation Speed<br/>(r/min):</li> </ul> | 3000 3600  |
| Phase No.:  | Single Phase   |
| <ul> <li>Power Factor:</li> </ul>                     | 1  |
| <ul> <li>Insulation Grade:</li> </ul>                 | F  |
| Pole Number:  | 2  |
| <ul> <li>Excitation Mode:</li> </ul>                  | Self-excitation & Constant Voltage (AVR)                 |
| <ul> <li>Panel Type:</li> </ul>                       | General Panel  |
| <ul> <li>Receptacle:</li> </ul>                       | Two Receptacles  |
| Connection Date:                                      |  |

## **GET9500T Silent Diesel Generator White Electric Start Silent Generator**

Quiet diesel generators come with various features and technologies that contribute to their reduced noise emissions. While the specific features may vary depending on the manufacturer and model, here are some common features found in quiet diesel generators:

Soundproof Enclosure: Quiet diesel generators are typically equipped with a soundproof enclosure or housing made of materials designed to absorb and dampen noise. The enclosure helps to contain the sound and prevent it from escaping, reducing noise levels significantly.

Acoustic Insulation: The soundproof enclosure is lined with acoustic insulation materials, such as foam or specialized noisereducing materials. These materials absorb sound waves, preventing them from bouncing around and reducing the overall noise level.

Smart Load and Speed Control: Some quiet diesel generators come with smart load and speed control features. These systems automatically adjust the engine speed and power output based on the load demand, optimizing fuel consumption and reducing noise levels during low-demand periods.

Noise Level Specifications: Quiet diesel generators are typically rated for noise levels, which are measured in decibels (dB). The noise level specification indicates the sound output at a specific distance from the generator, such as 7 meters (23 feet). Lower dB ratings indicate quieter operation.

| Lower ab raings maioate quiete    |  |  |  |
|-----------------------------------|--|--|--|
| Rated Frequency:                  | 50hz 60hz  |  |  |
| Max Output (kw):                  | 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7  |  |  |
| Rated Currency (A):               | 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6  |  |  |
| Phase No.:                        | Single Phase   |  |  |
| Insulation Grade:                 | F  |  |  |
| Excitation Mode:                  | Self-excitation & Constant Voltage (AVR)   |  |  |
| Receptacle:                       | Two Receptacles  |  |  |
| DC 12V Output:                    | Connection Pole Output   |  |  |
| Dry Weight (kg):                  | 164 150 150 153 161  |  |  |
| Noise Level (7m):                 | 72 DB  |  |  |
| Engine Type:                      | Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled                             |  |  |
| Displacement(ml):                 | 296 418 456 498 531  |  |  |
| Compression Ratio:                | 20:01, 19:01   |  |  |
| Starting System:                  | Electric Start   |  |  |
| Lube Oil Brand:                   | CD Grade Or SAE10W-30, 15W-40  |  |  |
| Starting Motor Capacity:          | 12V 0.9KW/ 12V 1.2KW   |  |  |
| Battery Capacity:                 | 12V 30Ah   |  |  |
| Fuel Tank Capacity (L):           | 15   |  |  |
| Rated Output(kw):                 | 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3  |  |  |
| Rated Voltage (V):                | 220V Or As Request   |  |  |
| Rated Rotation Speed (r/min):     | 3000 3600  |  |  |
| Power Factor:                     | 1  |  |  |
| Pole Number:                      | 2  |  |  |
| Panel Type:                       | General Panel  |  |  |
| Connection Pole:                  | Without  |  |  |
| Overall Dmension(mm):             | 945*555*700  |  |  |
| Working Assorting Weight (kg):    | 179 185 186 186 187  |  |  |
| Structure Type:                   | Silent Type  |  |  |
| Cylinder Nobore X Stroke<br>(mm): | 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75  |  |  |
| Rated Power:                      | 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-<br>8.7/3600 |  |  |
| Lubrication System:               | Pressure Splashed  |  |  |
| Fuel Type:                        | 0#(summer)-10#(winter)-35#(chillness) Diesel   |  |  |
| Lube Capacity (L):                | 1.1/ 1.65  |  |  |
| Charging Generator Capacity:      | 12V 8.3A   |  |  |
| Fuel Consumption (g/kw*h):        | ≤280   |  |  |
|                                   |  |  |  |



| Still Model  | OFTIMOT   | TIMOT                    | OFTNEE                 | BETHNOET          |               |
|--|---|--------------------------|------------------------|-------------------|---------------|
| B283 /Webciteguerry   He   |   |                          | 52 66                  |                   |               |
| BEER Paterinsted (10%)   | 2.8 2.8   | 4.0 4.8                  | 4.8 8.0                | 87 60             | 60.63         |
| BARRIE Man. mapril (1997)  | 3.7 30  | 10 13                    | 6.2 6.8                | 83.62             | 48.33         |
| BRIGH Plaint-schape ( 5 )  | LOV/DRWK PER 200/ or an request   |                          |                        |                   |               |
| Bill Bill Photo Survey 14.5  | TLS 127   | 204 218                  | 21.8 22.7              | 20.8 27.2         | 373.38.8      |
| EXTRA Partnerships agend Colver 1  | 2001 2800   |                          |                        |                   |               |
| BE Phone MC  | WEI DYCH JIGH   |                          |                        |                   |               |
| Site 2000 Provent Sector 1 Cost -0 2   |   |                          |                        |                   |               |
| Bill B Di Insulation Erach   |   |                          |                        |                   |               |
| DB Pos number  |   |                          | 8                      |                   |               |
| BREED Excession made   | (B.695.3.) (Bank) ( Set-auctuation & constant unless and it                                       |                          |                        |                   |               |
| Diskist Panel Type   | # 888 General Fand  |                          |                        |                   |               |
| et die Prostale  |   | Nº 00000 ES Tax montains |                        |                   |               |
| R & M M & Connection price   | 8 Autout  |                          |                        |                   |               |
| BEDE SIV DESIV odpit   |   | 80                       | RIMA Corrector pole to |                   |               |
| HER-H Granal dimension ( LowPublic Creek)  | 942-902-906   | 845/555798               | 941-555700             | 847/007/108       | 845-555798    |
| NE Dry anight I to I   | *64   | -12                      | +50                    | 123               | 182           |
| Light States printing analysis ( b) 1  | 178   | 185                      | 136                    | 484               | 182           |
| Bill William Management   Per  | 10  | 72                       | 10                     | 79                | 72            |
| PORT Tradest light   | Hard bare   |                          |                        |                   |               |
| DBRBA Dupe Mobil   | DETICH  | <b>GETINFA</b>           | CET HIMP               | 0071407           | GETHEF        |
| Indexed & Drugee Type  | Way, X.Y., May, 2016, (Advanted by a particular operation from drawn drawn pression, and pression |                          |                        |                   |               |
| NEE-IEE/WEED/WEED/CONFIGURATION  | 1-79'80   | 1-00"72                  | 1-88779                | 1-8075            | 1-81'75       |
| IN B Experience I and I  | 294   | 4.0                      | 450                    | 498               | 500           |
| of the second stand proof  | 3.55/3000 41800   | 5 20000-0-010000         | 4-5/9000 P (20000)     | 1 010000-01210000 | 81/00014-1008 |
| Citit & Compression ratio  | and a second  | 1001                     | 1991                   | 1004              | 10111         |
| A R R R Laboration system  | En Villehrd Presses schoted   |                          |                        |                   |               |
| Grand of chartery system   | 4 G in Earthe start   |                          |                        |                   |               |
| Ball for you   | 04 (201)-104 (201)-364 (203) 808 dead04 (sense)-364 (sinter)-364 (mines) dead                     |                          |                        |                   |               |
| internal internal internal   | CD mark or SM SIA 31, 1597-80   |                          |                        |                   |               |
| Contraction of the second seco | 1.1   | 1.61                     | 1.65                   | 1.65              | 1.05          |
| 101-11 distant when a set of the little  | 124 8.044   | 10/ 09/9                 | 101 6.000              | 124 1.244         | 107 1,000     |
| I&E B R.R.B. Charging generator stagestic [V-A]  | 107 8.34  | 124 8.56                 | 429 4.34               | GTV 8.34          | 124 8.56      |
| DR.R.R.B. Bulley-Learning Cor-Wol  |   | 101 3044                 |                        | UV                | MAG           |
| BERRE Functionarytics ( gite/%)  | +200  | < 380                    | <381                   | +280              | < 380         |
| TRAFFIC Fuelant specty [1.1  | 10  | 10                       | 15                     | 11                | 10            |
| NEEPERM COMMAND AWAY MILETY  | 11  | 1                        |                        |                   |               |

| <b>G</b> ET Wuxi Guangertai Power Machinery Co.,Ltd       |                         |                         |  |  |  |
|---|-------------------------|-------------------------|--|--|--|
| <b>()</b> 1381365   | 50506 2415819289@qq.com | e dieselenginepumps.com |  |  |  |
| NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA |                         |                         |  |  |  |

L