



13.5L High Pressure Inline Fuel Pump GET173F Electric Start

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Model Number: GETDP150
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Clean Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

High Pressure Inline Diesel Fuel Pump Diesel Fire Pump Electric Start

Wastewater Management: Electric diesel engine pumps are employed in wastewater treatment plants for pumping sewage, sludge, or wastewater. They help in the transfer of fluids within the treatment facility, as well as in the transportation of treated effluent for discharge or reuse.

Marine and Offshore: Electric diesel engine pumps are utilized in marine and offshore applications for various purposes, including bilge pumping, ballast water management, fire protection systems, and general fluid transfer on ships, vessels, and offshore platforms.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	

Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA