



50hz 60hz Genset Diesel Welder Generator 25V-30V Welding Voltage

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Power (kw): 2.5
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 8.7 9.5A
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- No Load Welding Voltage: 65-70V
- Insulation Grade: F
- Pole Number: 2
- Displacement(ml): 418 456
- Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
- Bore X Stroke (mm): 1-86x72/ 1-92x75
- Compression Ratio: 16:1

for more products please visit us on dieselenginepumps.com

Product Description

GET6500EAW Diesel Powered Welder Generator Pressure Splashed

The welding generator is a device that integrates power generation and welding functions. It has the following characteristics:

1. Energy saving and environmental protection: Many welding generators adopt energy-saving and environmentally friendly designs to reduce energy consumption and impact on the environment. They typically feature efficient combustion systems and noise control measures to provide reliable performance while reducing energy consumption and noise pollution.
2. High durability and reliability: Welding generators usually use durable materials and construction to ensure reliable operation in various harsh environments. They undergo strict quality control and testing and have a long service life and high reliability.
3. Safety protection functions: The welding generator is equipped with a variety of safety protection functions to ensure the safety of operators. These features include overload protection, short circuit protection, overheating protection, etc. to prevent equipment damage and personal injury.
4. Easy to operate and maintain: Welding generators usually have simple and easy-to-understand operating interfaces and control systems, making it easy for operators to operate and adjust. At the same time, they also have an easy-to-maintain design to facilitate daily maintenance and upkeep to ensure long-term stable operation of the equipment.
5. The characteristics of the welding generator make it a versatile, flexible and reliable device that is widely used in construction sites, manufacturing, agriculture and emergency maintenance to meet power supply and welding needs.

| | |
|-----------------------------------|--|
| Rated Power (kw): | 2 5 |
| Rated Current (A): | 8.7 9.5A |
| Phase No.: | Single Phase |
| No Load Welding Voltage: | 65-70V |
| Pole Number: | 2 |
| Displacement(ml): | 418 456 |
| Bore X Stroke (mm): | 1-86x72/ 1-92x75 |
| Rated Power: | 5.7 6.3/ 7.2 8.2 |
| Lube Oil Brand: | CD Grade Or SAE10W-30, 15W-40 |
| Fuel Type: | 0#(summer)-10#(winter)-35#(chillness) Diesel |
| Fuel Tank Capacity (L): | 13.5 |
| Rated Welding Current: | 180A 220A |
| Welding Load Continuous Ratio: | 60% |
| Electrode Diameter: | 1.6-3.2mm 1.6-5.0mm |
| Rectifying Mode: | Diode |
| Overall Dimension: | 720x492x655mm |
| Dry Weight: | 112kg 116kg |
| Rated Frequency: | 50hz 60hz |
| Rated Voltage (V): | 220V Or As Request |
| Rated Rotation Speed (r/min): | 3000 3600 |
| Power Factor: | 1 |
| Insulation Grade: | F |
| Engine Mode: | GET186FA GET192F |
| Engine Type: | Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled |
| Compression Ratio: | 19:01 |
| Lubrication System: | Pressure Splashed |
| Lube Capacity (L): | 1.65 |
| Fuel Consumption (g/kw*h): | ≤280 |
| Continuous Running Time: | 8h |
| Welding Voltage: | 25-30V |
| Welding Current Adjustment Range: | 50-180A/ 50-200A |
| Excitation Mode: | Seperate-excitation+AVR Voltage Regulation AVR |
| Connection Mode: | Drive Bearing, Rigid Connection |
| Structure Type: | Open Type |



參數表 Specifications

[illegible]